

## Product profile

# CK32

Intrinsically Safe  
Mobile Computer



- **Designed from inception to meet the most stringent, global certifications - UL, ATEX, IECEX**
- **Safest choice for workers in the chemical, oil and gas, and pharmaceutical industries**
- **Complements existing hazardous-certified and standard products allowing companies to standardize on one vendor or one form factor**
- **Supported by localized Intermec and Partner Service and Support Centers situated around the globe**

The Intermec CK32 Intrinsically Safe (CK32IS) mobile computer carries the most extensive list of global hazardous environmental ratings of any rugged mobile computer in the world - UL (Underwriter's Laboratory), ATEX (European Atmospheres Explosibles Directives) and IECEX (International Electrotechnical Commission) - making it the safest choice for workers in the chemical, oil and gas, and pharmaceutical industries.

The CK32IS meets or exceeds the most stringent requirements, not only for gases, vapors and liquids, but also for dusts, fibers and even, in certain regions, underground mining applications.

The highly durable construction of the CK32IS reflects the operational reality of these environments: breakage in a hazardous location is more than a matter of downtime and inconvenience; it's potentially lethal. The rugged CK32IS has achieved an IP67 sealing and 5 foot drop spec, and is the only mobile computer to achieve Zone 0 certification, which designates "double fault" safety in environments in which flammable gases are always present under normal operating conditions.

The CK32IS provides the optimum combination of real time operation, tools support and standard connectivity by incorporating all the leading industrial mobile computing technologies - Microsoft® Windows Mobile® operating system, 802.11 b/g, Bluetooth®, VoIP support, integrated scanning, USB and Ethernet.

The intelligent design of the CK32IS also allows users to easily install or remove scan handles and to replace batteries within a hazardous environment.

The CK32IS is complemented by the full Intermec family of rugged ADC devices for the enterprise, as well as additional mobile computers for hazardous environments. This allows customers to simply pick the appropriate form factor and certifications ratings for their specific application needs.

The CK32IS supports all the leading industry standards and development tools provided within Intermec's product offerings: SmartSystems™, Wavelink Avalanche Remote Device Management, Cisco® Compatible Extensions (CCX), Wi-Fi®, .NET, Java and the Intermec Developer Library (IDL). This commitment

allows customers to further maximize their investments by providing a strategy for ongoing, industry-leading technology updates, as well as support for fast application development and deployment. With the backing of Intermec's global service and support network for all products including the CK32IS, customers can confidently implement a long term, reliable solution across multiple operational environments and take advantage of the efficiencies of less product training, fewer product platforms, and simplified support and service.

#### Physical Description

The CK32IS is a rugged, intrinsically safe handheld mobile data collection computer, designed from inception to meet the most stringent global hazardous location requirements. It features the Windows Mobile 5.0 operating system and an Intel™ XScale™ PXA270 processor.

#### Physical Characteristics

**Length:** 240 mm (9.45 in)  
**Height:** 51 mm (2.02 in) at grip area  
**Width at grip:** 71 mm (2.8 in)  
**Weight:** 1.08 kg (38 oz)

#### Hardware

**Microprocessor:** Intel XScale PXA270 Processor  
**Memory:** 128 MB DRAM, 64 MB non-volatile Flash  
**Memory/Storage extensions:** 512MB embedded SD Flash Memory Card  
**Display:** 240 x 320 (1/4 QVGA) backlit transfective display with 3.5" diagonal supporting 16-bit color depth (65K colors) and resistive panel touch screen. Tethered stylus included.  
**Keypad:** 42-key and 56 key with Standard, VT/ANSI, 3270/5250 Overlay Configurations

#### Operating System

Microsoft® Windows Mobile 5.0

#### Software

**Terminal Emulation:** Supports Intermec TE2000 and third party VT/ANSI, IBM 5250/ 3270.  
**Browser support:** Internet Explorer Mobile  
**Software Development Kit:** Intermec Development Library (IDL). Supports device specific features and bar code scanning.

#### Bar Code Scanning

Integrated Linear Imager

#### Standard Communications

Ethernet  
USB Client  
Bluetooth®  
802.11 b/g

#### Wireless Certifications

Wi-Fi  
WPA2  
Cisco Compatible Extensions CCX v3

#### Device Management

**SmartSystems™ Support:** Centralized remote support capability; Configures, updates and maintains single devices or entire populations; Real-time or batch, wired or wireless; Wavelink Avalanche™ with Intermec's value added utilities

#### Audio System

**All audio paths are present to support:** interactive VoIP, walkie talkie, digital recording, AV playback. Microphone support for voice communications and speech recognition applications. Voice quality speaker with volume control and speaker capable of reproducing voice and WAV files.

#### Power

**Battery Type:** Lithium-Ion, 7.5V, 2400 mAh; User replaceable in hazardous environments

#### Environment

**Operating Temperature:** -20° to 50°C (-4° to 122°F)  
**Storage Temperature:** -20° to 70°C (-4° to 158°F)  
**Relative humidity:** 5 - 95% (non-condensing)  
**Environmental protection:** IP67  
**Drop Survival:** Multiple 5' (1.52 m) drops to ¼ inch steel plate bonded to a concrete slab  
**Vibration and shock protection:** Tested to MIL-PRF-28800F standards

#### Accessories

**Chargers:** Model AC11 4-slot battery charger  
**Communications Adapter Model AN1:** Required for USB and Ethernet.  
**User Accessories:** Pistol grip handle; carrying strap; hand strap; user replaceable touch panel protection cover, AB6 spare battery, battery eliminator

#### Regulatory Compliance

Compliant with all EU Directives including ATEX IECEx Certified  
FCC Part 15/ICES-003/EN55022/CISPR 22 Class A  
UL 913 Certified

**Regulatory Compliance - Pending**  
NOM-NYCE

#### Hazardous Location Certifications (ATEX/IECEx)

Zone 0, IIC, T4  
Zone 20, T250°C  
Group I M1

#### ATEX Countries

**Approved:** Europe, Turkey, Norway, Switzerland, Czech Republic

#### IECEx Countries

**Approved:** New Zealand, Australia, Singapore, Malaysia  
**Pending:** Saudi Arabia, South Africa, Thailand, UAE, Brazil, China, South Korea, Indonesia, Philippines

#### Hazardous Location Certifications (UL)

Class I, Division 1, Groups A, B, C, D - T4  
Class I, Zone 0, Group IIC, T4  
Class II, Division 1, Groups E, F, G - T4  
Class III, Division 1

#### UL Countries

**Approved:** U.S., Canada  
**Pending:** Mexico

#### North America

**Corporate Headquarters**  
6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348-2600  
Fax: (425) 355-9551

#### South America & Mexico

**Headquarters Office**  
Newport Beach, California  
Phone: (949) 955-0785  
Fax: (949) 756-8782

#### Europe/Middle East & Africa

**Headquarters Office**  
Reading, United Kingdom  
Phone: +44 118 923 0800  
Fax: +44 118 923 0801

#### Asia Pacific

**Headquarters Office**  
Singapore  
Phone: +65 6303 2100  
Fax: +65 6303 2199

#### Internet

www.intermec.com  
Worldwide Locations:  
www.intermec.com/locations

#### Sales

Toll Free NA: (800) 934-3163  
Toll in NA: (425) 348-2726  
Freephone ROW: 00 800 4488 8844  
Toll ROW: +44 134 435 0296

#### OEM Sales

Phone: (425) 348-2762

#### Media Sales

Phone: (513) 874-5882

#### Customer Service and Support

Toll Free NA: (800) 755-5505  
Toll in NA: (425) 356-1799

**Intermec®**  
SmartSystems™



Copyright © 2007 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611825-01C 06/07

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

**Intermec®**