SKORPIO[™] X4

DATALOGIC



CHOICE OF WINDOWS EMBEDDED OR ANDROID™ OPERATING SYSTEMS

The Skorpio[™] X4 mobile computer features a high performance multicore 1 GHz architecture that offers blazing speed when running Windows Embedded Compact OS and allows easy upgradeability to the Android OS. Users will never run out of memory with the standard 1 GB RAM and 8 GB Flash.

OUTSTANDING USER INTERFACE

Equipped with the largest high-visibility 3.2 inch color display touch screen in its class, the Skorpio X4 mobile computer helps users work more efficiently.

Three different keyboards are available for maximum efficiency: a 50-key alphanumeric keypad, a 38-key functional keypad and a 28-key numeric keypad.

ERGONOMIC AND RELIABLE

This rugged mobile computer is particularly suitable for mobile commerce solutions in the retail environment both in-store and back-end receiving applications. With the best ergonomics on the market, the Skorpio X4 mobile computer reduces operator fatigue with no compromise in terms of reliability and robustness, resisting harsh environments, multiple drops, strong shocks and repetitive tumbles. The pistol-grip model has the most durable and comfortable handle in the industry.

WIRELESS COMMUNICATION

The Skorpio X4 mobile computer's wireless communication capabilities (802.11 a/b/g/n) enables speedy transmission of data, while *Bluetooth®* wireless technology v4 provides support for the new low energy mode (BLE). The new MIMO antennas provide extended coverage.





FEATURES

- Large high visibility color display with touch screen
- Choice of 1D or 2D imagers featuring Datalogic's patented 'Green Spot' technology for good-read feedback
- Wide Band Audio for improved speech recognition (Android[™] only)
- Choice of Microsoft Windows Embedded Compact 7 or Android v4.4 operating systems
- TI 802.11 a/b/g/n radio with CCX v4 and featuring MIMO antenna technology
- Bluetooth wireless technology v4.0 with BLE (low energy) on Android models
- 1.8 m / 6.0 ft drop resistance
- IP64 protection class
- WEC7 units include:
 - Wavelink[®] Avalanche[™] pre-installed and pre-licensed
 - Wavelink TelnetCE pre-installed and prelicensed on Pistol Grip units
 - Pal[™] pre-installed
 - Upgradable to Android 4.4
- Attachable handle (and orderable pre-installed)
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY-APPLICATIONS

- Inventory/Picking
- Shelf replenishment
- Price management
- Order entry
- Assisted sales
- Line busting
- Shipping/Receiving

SKORPIO™ X4

OIDOJATACO

WIRELESS COMMUNICATIONS		READING PERFORMANCE	
LOCAL AREA NETWORK (WLAN) PERSONAL AREA NETWORK (WPAN)	TI Wi-Link 8, IEEE 802.11a/b/g/n; Frequency Range: Country dependent, typically 2.4 and 5 GHz; Cisco Compatible CCX v4 Security <i>Bluetooth</i> v4 with BLE (Android models); <i>Bluetooth</i> v2.1 + EDR (WEC7 models)	2D IMAGER (STANDARD RANGE)	Megapixel sensor for extended range; White LED Illumination Optical Resolution: 1D codes: 3 mils; 2D codes: 6.6 mils Depth of Field (typical): 4.5 to 74 cm / 1.7 to 29.1 in (13 mil/EAN), depending on bar cod
DECODING CAPABILITY			density and type
1D / LINEAR CODES 2D CODES	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes. Aztec Code, Data Matrix, MaxiCode, PDF417, MicroPDF417, Micro QR Code, QR Code	1D IMAGER	2500 pixel sensor; Sharp green LED scan line Optical Resolution: 2.5 mils (linear codes) Depth of Field: 4.0 to 74 cm / 1.5 to 29.1 in (13 mil/EAN), depending on bar code density
POSTAL CODES	Australian Post, Japanese Post, KIX Code, Royal Mail, USPS Intelligent Mail, USPS PLANET, USPS	SAFETY & REGULATORY	and type
	POSTNET	AGENCY APPROVALS	The product meets necessary safety and
GS1 COMPOSITE CODES	UPC/EAN/JAN Composites, GS1 DataBar Composites and GS1-128 Composite (Composites supported on WEC7 only)	ENVIRONMENTAL COMPLIANCE LASER CLASSIFICATION	regulatory approvals for its intended use. Complies to EU RoHS VLD - Class 2 IEC/EN60825-1; Compliant with 2 CFR 1040.10 except for deviations pursuant to
ELECTRICAL		LED CLASSIFICATION	laser notice No. 50 dated June 24, 2007. Exempt Risk Group IEC/EN62471
BATTERY	Removable battery pack with rechargeable Li- Ion batteries; MicroUSB for fast battery charging	SOFTWARE	
	Standard: 3.7 V; 3,000 mAh (11.1 Watt-hours); standard on all handheld models Extended: 3.7 V; 5,200 mAh (19.2 Watt-hours); standard on all Pistol Grip models	APPLICATIONS CONFIGURATION & MAINTENANCE	Pal Application Library pre-licensed (WEC7 only Wavelink Avalanche® pre-licensed (WEC7 only), 42 Gears SureLock pre-licensed for device lockdown (Android only); SOTI MobiControl,
ENVIRONMENTAL			Datalogic xPlatform Utility (DXU) pre-licensed, Datalogic Desktop Utility (DDU) pre-licensed for
DROP RESISTANCE	Withstands drops from 1.8 m / 6.0 ft onto concrete	DEVELOPMENT	device lockdown (WEC7 only) WEC7: Datalogic Windows SDK™,
PARTICULATE AND WATER SEALING TEMPERATURE	IP64 Operating: -10 to 50 °C / 14 to 122 °F Storage: -20 to 70 °C / -4 to 158 °F	BROWSER	Wavelink® Studio™, MCL-Collection™ Android: Datalogic Android SDK, Xamarin SDK SureLock locked web browser pre-licensed for
		TERMINAL EMULATION	WEC7 and Android models Wavelink® Terminal Emulation™ pre-licensed (fo
			Pistol Grip/WEC7 models only);
INTERFACES	Main connector with USB 2.0 High Speed Host (480 Mbps) and Client, RS-232 up to 115.2 Kbps; microUSB port for power and communications; Ethernet: via single dock (external module) or multi-slot dock	CVCTEN	StayLinked SmartTE (for Android)
		AUDIO	Wideband Speech (HD Audio) supported on
	Hald Slot dock		Android
PHYSICAL CHARACTERISTICS		EXPANSION SLOTS MICROPROCESSOR	Micro Secure Digital slot (SDHC) up to 32 GB TI OMAP4 @ 1 GHz
DIMENSIONS	Handheld: 19.3 x 7.6 x 4.2 cm (6.1 x 3.5 cm at keyboard) / 7.6 x 3.0 x 1.3 in (2.4 x 1.4 in at keyboard)	MEMORY	RAM Memory: 1 GB Flash Memory: 8 GB (partially used for firmware and reserved data)
DISPLAY	Pistol Grip: 19.3 x 7.6 x 15.6 cm / 7.6 x 3.0 x 6.2 in TFT / Transflective LCD with 240 x 320 pixel	OPERATING SYSTEM	Microsoft Windows Embedded Compact 7 (WEC7) or Android v4.4*
	resolution; LED backlight and integrated touch screen, 3.2 inch diagonal		from Android 4.4 to WEC7 is supported on all p must be performed at a Datalogic Service Center.
KEYBOARD	50-key full alphanumeric, 38-key functional or 28-key numeric keyboard with backlight		
WEIGHT	Handheld (with standard battery): 388 g / 13.7 oz	WARRANTY	
	Handheld (with hi-cap battery): 422 g / 14.9 oz Pistol Grip (with standard battery): 482 g / 17.0 oz Pistol Grip (with hi-cap battery): 516 g / 18.2 oz	WARRANTY	1-Year Factory Warranty
		Caution: Laser Radiatio	on - do not stare into beam
Base Stations/Chargers 94A150062 Single Slot Dock with Spare Battery Slot		Cases/Holsters 94ACC0050 Holster 	Miscellaneous • 95ACC0002 Headset VXI VR12
 94AfS0062 Single Side Dott With Si 94AfS0079 Optional Ethernet Adap 94A150055 Four Slot Ethernet Docl 94A150034 Multi Battery Charger 	otor for Single Slot Dock	• 94ACC0052 Rubber Boot	9AACC0127 Bluetooth Headset VXI B350XT EL 94ACC0124 Bluetooth Headset VXI B350XT US 94ACC0124 Bluetooth Headset VXI B350XT US
			K.K.

© 2017 Datalogic S.p.A. and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. • Skorpio is a trademark of Datalogic S.p.A. and/or its affiliates. • SoftSpot is a trademark of Datalogic S.p.A. and/or its affiliates, registered in the E.U. • Android is a trademark of Google Inc. • The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Group companies is under license. • All other trademarks and brands are property of their respective owners • Product specifications are subject to change without notice. • DS-SKORPIOX4-ENA4 Revision A 20170918

www.datalogic.com